



# Fly With Confidence



## INSTRUCTION


- 1 HOLD UPRIGHT. PULL RING PIN.
- 2 START BACK 8 FEET. AIM AT BASE OF FIRE.


H  
A


# HALON 1211 FIRE EXTINGUISHERS


- Halon 1211 fire extinguishers offer unmatched fire fighting performance
- Contain Halon 1211 recycled in accordance with the Montreal Protocol
- UL listed and tested to UL 711 and UL 1093
- Pressure gauge enables easy confirmation of charge
- FAA-accepted per FAA Advisory Circular: AC 20-42D





<b>A344T</b>		<b>2B:C</b> Cockpit/Cabin
Agent weight	1.25 lb.	
Gross weight	2.3 lb.	
Discharge range	9-12 ft.	
Discharge time	10 sec.	
Height	10.25 in.	
Width	3.9 in.	
Cylinder diam.	2.6 in.	


<b>A344TC</b>		<b>2B:C</b> Cockpit/Cabin
Agent weight	1.25 lb.	
Gross weight	2.3 lb.	
Discharge range	9-12 ft.	
Discharge time	10 sec.	
Height	10.25 in.	
Width	3.9 in.	
Cylinder diam.	2.6 in.	


<b>C352TS</b>		<b>5B:C</b> Cockpit/Cabin
Agent weight	2.5 lb.	
Gross weight	5.0 lb.	
Discharge range	9-15 ft.	
Discharge time	10 sec.	
Height	14.5 in.	
Width	4.5 in.	
Cylinder diam.	3.0 in.	


<b>C352TSC</b>		<b>5B:C</b> Cockpit/Cabin
Agent weight	2.5 lb.	
Gross weight	5.0 lb.	
Discharge range	9-15 ft.	
Discharge time	10 sec.	
Height	14.5 in.	
Width	4.5 in.	
Cylinder diam.	3.0 in.	

<b>C354TS</b>		<b>5B:C</b> Cockpit/Cabin
Agent weight	3.0 lb.	
Gross weight	5.6 lb.	
Discharge range	9-15 ft.	
Discharge time	12 sec.	
Height	14.4 in.	
Width	6.3 in.	
Cylinder diam.	3.0 in.	

<b>B355T</b>		<b>10B:C</b> Cockpit/Cabin
Agent weight	5.0 lb.	
Gross weight	8.8 lb.	
Discharge range	9-15 ft.	
Discharge time	10 sec.	
Height	15.3 in.	
Width	5.8 in.	
Cylinder diam.	4.25 in.	

<b>B369</b>		<b>10B:C</b> Ramp/Cargo
Agent weight	9.0 lb.	
Gross weight	16.75 lb.	
Discharge range	12-18 ft.	
Discharge time	9 sec.	
Height	16.3 in.	
Width	8.5 in.	
Cylinder diam.	5.0 in.	

<b>B371</b>		<b>2A:40B:C</b> Ramp/Cargo
Agent weight	13.0 lb.	
Gross weight	22.1 lb.	
Discharge range	12-18 ft.	
Discharge time	14 sec.	
Height	20.3 in.	
Width	8.5 in.	
Cylinder diam.	5.0 in.	


<b>361</b>		<b>4A:80B:C</b> Ramp/Cargo
Agent weight	17.0 lb.	
Gross weight	34.8 lb.	
Discharge range	12-18 ft.	
Discharge time	22 sec.	
Height	23.9 in.	
Width	9.8 in.	
Cylinder diam.	7.0 in.	


# HALON ALTERNATIVE FIRE EXTINGUISHERS


## HALOTRON® 1


- The most widely deployed and the least expensive Halon 1211 alternative
- UL listed and tested to UL2129 & UL711




<b>A384T</b>		<b>1B:C</b> Cockpit/Cabin
Agent weight	1.4 lb.	
Gross weight	2.6 lb.	
Discharge range	6-8 ft.	
Discharge time	9 sec.	
Height	10 in.	
Width	3.5 in.	
Cylinder diam.	2.6 in.	

<b>B385TS</b>		<b>2B:C</b> Cockpit/Cabin
Agent weight	2.5 lb.	
Gross weight	5.4 lb.	
Discharge range	6-10 ft.	
Discharge time	9 sec.	
Height	14.8 in.	
Width	5.0 in.	
Cylinder diam.	3.0 in.	

<b>B394TS</b>		<b>5B:C</b> Cockpit/Cabin
Agent weight	5.5 lb.	
Gross weight	9.3 lb.	
Discharge range	9-15 ft.	
Discharge time	9 sec.	
Height	15.0 in.	
Width	5.13 in.	
Cylinder diam.	4.25 in.	


<b>397</b>	<b>1A:10B:C</b> Ramp/Cargo	
Agent weight	11 lb.	
Gross weight	22.5 lb.	
Discharge range	9-15 ft.	
Discharge time	9 sec.	
Height	21.9 in.	
Width	9.25 in.	
Cylinder diam.	6.0 in.	


<b>398</b>	<b>2A:10B:C</b> Ramp/Cargo	
Agent weight	15.5 lb.	
Gross weight	27.5 lb.	
Discharge range	12-18 ft.	
Discharge time	14 sec.	
Height	21.9 in.	
Width	9.25 in.	
Cylinder diam.	6.0 in.	


## HALOTRON® BRX


- The smallest, lightest and the most effective Halon 1211 alternative
- UL listed and tested to UL2129 & UL711



<b>337TS</b>	<b>2:BC</b> Cockpit/Cabin	
Agent weight	1.92 lb.	
Gross weight	3.18 lb.	
Discharge range	7-8 ft.	
Discharge time	9 sec.	
Height	11.25 in.	
Width	4.0 in.	
Cylinder diam.	3.25 in.	

<b>347TS</b>	<b>5:BC</b> Cockpit/Cabin	
Agent weight	3.75 lb.	
Gross weight	5.5 lb.	
Discharge range	10-12 ft.	
Discharge time	9 sec.	
Height	17.6 in.	
Width	4.0 in.	
Cylinder diam.	3.25 in.	

<b>349TS</b>	<b>5:BC</b> Cockpit/Cabin	
Agent weight	3.75 lb.	
Gross weight	5.75 lb.	
Discharge range	10-12 ft.	
Discharge time	9 sec.	
Height	17.6 in.	
Width	5.9 in.	
Cylinder diam.	3.25 in.	

<b>351</b>	<b>2A:10:BC</b> Ramp/Cargo	
Agent weight	12.5 lb.	
Gross weight	19.88 lb.	
Discharge range	15-17 ft.	
Discharge time	16 sec.	
Height	20.25 in.	
Width	8.5 in.	
Cylinder diam.	5.0 in.	

# WHEELED EXTINGUISHERS

Wheeled fire extinguishers offer outstanding fire stopping power in a convenient towable package optimized for on-demand flight line protection.

## HALOTRON® 1

- Most popular wheeled flight line extinguishers
- Can be found at airports throughout the world
- Low Global Warming Potential (GWP)
- Low Ozone Depletion Potential (ODP)
- Short atmospheric lifetime



### B673

### 4A:80B:C

Agent weight	65.0 lb.
Gross weight	286.0 lb.
Discharge range	30-45 ft.
Discharge time	22 sec.
Height	58.0 in.
Width	28.0 in.
Depth	39.0 in.



### B674

### 10A:120B:C

Agent weight	150.0 lb.
Gross weight	512.0 lb.
Discharge range	30-45 ft.
Discharge time	38 sec.
Height	64.0 in.
Width	30.0 in.
Depth	42.0 in.



## NOVEC™ 1230

- Zero ozone depletion potential (ODP)
- 5-day atmospheric lifetime (vs. 65 years for halons)
- Global warming potential of 1 (similar to naturally-occurring CO2)
- No regulations or phase-down measures globally



### 775

### 3A:80B:C

Agent weight	150.0 lb.
Gross weight	395.0 lb.
Discharge range	30 ft.
Discharge time	22 sec.
Height	59.0 in.
Width	29.0 in.
Depth	42.0 in.





# MOUNTING OPTIONS

## FAA DAR Tested Bracket

- **Model BKT325** fits H3R Aviation fire extinguisher models 347TS and 349TS and Kidde Technologies fire extinguisher model 476288
- Successfully tested to the requirements defined in Title 14 CFR Part 23, 25, 27 and 29



## Box-type Brackets

- **Model 809** fits B369, B371 and 351 fire extinguishers
- **Model 810** fits model 361 fire extinguisher
- **Model 812** fits 397 and 398 fire extinguishers



## Extreme Duty Brackets

- **Not certified** for use on aircraft - experimental aircraft only
- **Model NB300** fits C352TS/C, C354TS and B385TS/C
- **Model NB350** fits model P3APP003010A
- **Model NB425** fits B355T & B394TS
- **Model NB500** fits B369, B371 & 351

